HK INSTRUMENTS

HUMIDITY TRANSMITTERS RHT DUCT SERIES

Duct mount relative humidity transmitters for building automation systems

RHT Duct is a relative humidity transmitter with temperature output installed in air ventilation duct. In addition to these measured values, RHT Duct calculates various parameters such as dew point, mixing ratio, enthalpy and absolute humidity. Illuminated display ensures easy readability also from a distance. The RHT has a screwless lid and an easily adjustable mounting flange that make the installation of the device easy.

RHT Duct series devices include:

- Two selectable voltage outputs (0-10 V / 2-10 V / 0-5 V) for measured and calculated parameters (rH, T, dew point, mixing ratio, enthalpy and absolute humidity).
- Offset feature enabling field calibration for measurement parameters rH and T.
- Mounting flange

RHT Duct series device options offer:

- Clear backlit display
- Modbus configuration
- Two selectable current outputs (4-20 mA) for measured and calculated parameters.

APPLICATIONS

RHT Duct series devices are commonly used to monitor and control:

• Relative humidity and temperature levels of incoming and return air in ventilation system

MODEL SUMMARY

	RHT Duct	-	RHT Duct with mA output	
Description	Model	Product code	Model	Product code
Relative humidity transmitter for duct	RHT Duct	302.002.001	RHT-Duct-A	302.008.005
- with display	RHT Duct-D	302.002.002	RHT Duct-A-D	302.008.006
- with Modbus configuration and display	RHT-MOD Duct-D	302.002.006		





HUMIDITY TRANSMITTERS RHT DUCT SERIES

SPECIFICATIONS

Performance

Measurement ranges: Temperature: -30...80 °C, sensor Relative humidity: 0-100 % Accuracy: Temperature: <0.5 °C Relative humidity: ±2...3 % at 0...50 °C and 10-90 % rH Total error band includes accuracy, hysteresis and temperature effect over 5...50 °C and 10-90 % rH.

Technical Specifications

Media compatibility: Dry air or non-aggressive gases Measuring units: °C and % rH Measuring element: Temperature: NTC10k Relative humidity: Thermoset polymer capacitive sensing element Environment: Operating temperature: 0...50 °C Storage temperature: -20...70 °C Humidity: 0 to 95 % rH, non condensing

Physical

Dimensions: Case: 119 x 95.5 x 45 mm Probe: L=188 mm, d=12 mm Mounting: With flange, adjustable 40...155 mm Weight: 150 g Materials: Case: ABS Cover: PC Probe: ABS Mounting flange: LLPDP Protection standard: **IP54** Electrical connections: 4 spring loaded terminals (24 V, GND, OUT1*, OUT2*) 0.2-1.5 mm2 (16-24 AWG) A-model: 2 additional spring loaded terminals for mA-output (OUT1*, OUT2*) 0.2-1.5 mm2 (16-24 AWG) *Default OUT1=rH, OUT2=TE Outputs selectable on the display: temperature / dew point / mixing ratio / enthalpy / absolute humidity / relative humidity

Electrical

Supply voltage: 24 VAC or VDC $\pm 10 \%$ Current consumption: max 90 mA (at 24 V) + 10 mA for each voltage output Output signals for every media: 0/2...5/10 VDC, Load R minimum 1 k Ω Only A-model: 4...20mA, Load R maximum 500 Ω , minimum 20 Ω Output calibrated within ± 0.08 mA

Conformance

Meets requirements for:						
	CE:	UKCA:				
EMC:	2014/30/EU	S.I. 2016/1091				
RoHS:	2011/65/EU	S.I. 2012/3032				
WEEE:	2012/19/EU	S.I. 2013/3113				

COMPANY WITH MANAGEMENT SYSTEM CERTIFIED BY DNV ISO 9001 - ISO 14001



HOW TO GENERATE A MODEL?

Example: RHT Duct-D	Product Series						
	RHT	Relative humidity transmitter, analog configurations					
	RHT-MOD	Relative humidity transmitter, Modbus configuration					
		Mounting					
		Duct	Duct moun	unt			
			Output				
				Voltage output Voltage and current output			
			-A				
				Display			
				-D	With display		
					Without display		
Model	RHT	Duct		-D			

PRC Technologies Corp., Ltd. ลาดพร้าว 101 กรุงเทพ 10240 www.prctech-th.com โทรศัพท : 02 530 1714, 02 932 1711 มือถือ : 086 360 8600 อีเมล : contact@prctech.net LINE ID1: prctec-info, LINE ID2 : @prctec